



Pure & Original

DEAD FLAT ECO SEALER

PROTECTIVE SEALER SERVING DECORATIVE TECHNIQUES AND PAINT FINISHING

A premium quality, 100% acrylic, non-yellowing, water solvent sealer formulated by the best possible brightness with as little gloss as possible.

Look: Dead Flat Eco Sealer has an exceptional advantage, it does not gloss with friction and is scratch resistant. Dead Flat Eco Sealer can be cleaned with water and classical non-aggressive cleaning products.

Colors: none, makes the underlying color look more intensely.

Application: suitable on wall paints, lime paints and wooden foundations. Apply on lime and chalk paint in several thin equal layers. Drying time minimally 12 hours between layers.

Bathrooms

The sealer can be applied in bathrooms, if the aeration is very good.

Note: sealer is not suitable for use on inside shower walls.

Kitchens

The sealer can be applied in kitchens, behind the sink, etc. however only up to a temperature of maximally 100°C.

Storage: Keep in original packaging and on a dry and frost free place: minimally 12 months

Waste: Let left-over paint dry and have it picked up or bring it to an authorized processor.

Please note: Store out of reach of children. When it comes into contact with the eyes rinse well with water. Do not breath vapour and spray. Avoid contact with surface water.

Environment

VOS class a. Maximum allowed amount per 2010 p. L. 30g/l. This product contains maximally 30 grams/liter.

Packaging: available in 1L and 2.5L



Application

Apply 2 thin layers of Dead Flat Eco Sealer with (lime long-haired) brush or spray.

Airless: spray angle: 25° - 40° Nozzle: 0.011 – 0.015
Pressure: 100-150 bar High pressure Nozzle : 2.0 – 2.5 mm Pressure : 5 bar
Low pressure Nozzle: 2.0 – 2.5 mm

Do not use on horizontal surfaces where water remains. To obtain a result that is as flat as possible the last layer needs to be applied as thin as possible.

Please note, a white haze can arise when layers are applied too quickly an unevenly.



FRESCO - LIME PAINT



Application on lime paint and Marrakech walls

The underlying paint must be dry for at least 7-10 days, preferably 20 days.

Always test product in advance.

1st layer of dead flat eco sealer: dilute 30% with water

2nd layer of dead flat eco sealer: dilute 10% with water

Product characteristics

- Dead flat eco sealer makes the underlying color look more intensely.
- Wood becomes washable
- Friction doesn't result in gloss
- Makes surface maintenance friendly

Gloss: flat

Color: transparent

Basic characteristics on white paint at 20° C

Specific gravity: +/- 1,06g/cm³

Theoretical consumption: 12-15m²/L

Drying time-dust free: 30min – 1h

Repaintable: at least 10min

Ignition point: none

pH: 7-9

Technical advice

Not all occurring sub surfaces and their pre-treatment can be included in this technical sheet. Please consult your dealer for advice on specific situations and conditions. This technical sheet has been compiled to the latest paint technology.

Pure & Original accepts no responsibility or liability for any direct or indirect damage that may occur when using or interpreting the information provided. Application and processing techniques are beyond our control and large differences in the nature of the sub surfaces could demand adaptation of a professional processing technique.

For further information please visit the Pure & Original website www.pure-original.com